

Valuable functions, value-priced.

Fax machine. Printer. Copier. Scanner.

At the heart of the Xerox FaxCentre® F116 multifunction device is a robust and powerful fax machine. Yet – with its quick network-capable printing, convenience copying, color scanning, email and internet access – it opens the door to a multitude of critical desktop resources for the single user or small office. All in a compact and truly affordable package.





Specifications

FAX
Compatibility: ITU - T.37
Modem Speed: 33.6 Kbps
Compression: MMR/MR/MH/JBIG
JPEG for color fax transmission
Transmission: 3 seconds per page
Dual Lines: Yes on F116L,
No on F116

Resolutions
Mono:
Standard (100 x 200 dpi)
Fine (200 x 200 dpi)
Super Fine (400 x 200 dpi)
Photo Mode (200 x 200 dpi)
Color:
Standard (100 x 100 dpi)
Fine (200 x 200 dpi)
Super Fine (300 x 300 dpi)
Halftones: 256 levels
Fax Memory: 8 MB (550 pages
of ITU-T chart 1 with standard
resolution)
Memory Receive: Yes (Receive faxes
while printing other jobs from direct
connect or network)
Set Prefix Option: Yes
One Touch Dials: 26
Speed Dials: 500 entries with
Alphanumeric search
Color Fax Tx/Rec: Yes/No
Battery Back up: None req'd. Constant,
battery = free memory for jobs
Auto reduction receive: Yes,
Documents automatically reduced
to fit the recording (loaded) paper size
Device Access/Security (Secure fax):
32 mailboxes (1 public, 31 private
password-protected)
Up to 98 user codes or Dep't. codes
Can Also:
Lock printing of received faxes
Lock Keyboard
Lock number keypad
Lock internet settings

CONVENIENCE PRINTING
Technology: Laser Monochrome
Speed: 16 pages per minute (ppm)
Resolution: 600 x 600 dpi
PDL: GDI (Std), PCL and PS emulation
as option
Print Memory: 32 MB
Duplex: No
Connectivity - Standard: Direct connect
- via USB
Connectivity - Optional: Internal NIC

CONVENIENCE COPYING
Speed: 16 ppm
Resolution: 300 x 300 dpi
Reduce/Enlarge: 25-400% in 1%
increments
Multiple Copies: Up to 99 copies
Productivity: Scan Once/Print Many

CONFIGURATIONS	FaxCentre® F116	FaxCentre® F116/L
Copy/Print Speed	16 ppm	
First copy out time	21 seconds	
Resolution	300 x 300 dpi copy / 600 x 600 dpi print	
Processor	92 Mhz	
Connectivity	Direct Connect via USB; optional internal NIC	
Scan Resolution	300 x 300 dpi optical; 600 x 600 dpi interpolated	
Scan to e-mail	yes	
Fax Speed	33.6 Kbps	
Resolution	up to 400 x 200 dpi monochrome or up to 300 x 300 dpi color	
Transmission	3 seconds per page	
Dual Lines	No	Yes
Paper Handling		
Paper input capability	250 sheets	
Paper output	100 sheets	
Productivity		
Special features	Color scan to email	
Optional Accessories	Optional 500-sheet paper tray	
Duty Cycle	2500 pages / month	

SCANNING (Color and Monochrome)

Avg. Scan Speeds:
100 x 200 dpi: 1.8 seconds per page
300 x 300 dpi: 5.4 seconds per page
Color: 16 seconds per page
Maximum Resolution: Optical 300 x 300
600 x 600 Interpolated
Scan Driver: TWAIN Standard
Scanning Software Document
Management and OCR: ScanSoft®
PaperPort® and OmniPage® Software

EMAIL

Compatibility: ITU T37
Mail Protocol - sending: SMTP
SMTP Authentication:
Yes (only RFC 1734)
Mono email format: TIFF-F, PDF
Color email Format: JPEG

LAN ACCESS

Ethernet: 10 BaseT/100BaseT
Plug & Play configuration: Yes
(DHCP and BOOTP)
Internet Protocol: TCP/IP
DNS Queries: Yes (2 DNS servers access)
NETBIOS compatibility
(for name management): Yes
Respond to PING request: Yes

MEDIA HANDLING

Input Paper Capacity
Main Tray: 250 sheets
Minimum Size: 5 x 8 in / 120 x 208 mm
Maximum Size: 8.5 x 39.4 in /
216 x 1000 mm
Weights: 60 x 90 gsm / 16-24 lb bond
Bypass Tray: 1 sheet
Envelope feeding: Yes
(using bypass tray)
Additional Tray 2 (optional): 500 sheets
Automatic Document Feeder: 40 sheets
Output Capacity: 100 sheets

PHYSICAL CHARACTERISTICS

Footprint: 15 3/8 x 18 1/8 x 15 3/8 in. /
389 x 460 x 390 mm
Weight: 24.3 lb / 11 Kg (machine only)

ELECTRICAL

Power Switch: Yes
Power Requirements:
220 to 240 VAC, 50/60 Hz
(Europe & Latin America)
100 to 127 VAC, 50/60 Hz
(N. America)
Maximum Power Consumption:
850 watts
Power Saver Mode: 15 watts or less
Energy Saver: ENERGY STAR®
Compliant

OPERATING ENVIRONMENT

Temperature: 50° - 89.6°F, 10° - 32°C
Humidity: 20 - 80%

GENERAL SPECIFICATIONS

Total Device Memory: 32 MB SDRAM;
64 MB Flash Memory
Device Management:
Companion Pro Software

SUPPLIES

Approximate Yields
Toner-Starter Kit: 2,000 prints*;
Replacement Kit: 6,000 prints*
Drum Cartridge-Starter: 4,000 prints*;
Replacement Photoreceptor/Drum
Cartridge: 20,000 prints*

* Capacities are approximate, based on 5% cover-
age on an A-size page and dependent on customer
job mode run length

AGENCY APPROVALS

UL Safety / CSA Safety

Reduce operating costs and save space by consolidating functions into one powerful, office machine.

Robust and affordable All the essentials at one low price.

- 33.6 Kbps faxing provides quick transmission of multi-page documents in as little as 3 seconds a page
- Secure fax with 31 password-protected mailboxes to receive documents confidentially
- Dual-line fax capabilities on F116L means that two lines are always available for transmission and/or reception
- Outstanding laser technology and PCL6 printing from PC or network for highest quality documents
- Scanning in full color (or black-and-white) to email via the internet

Productivity-boosting High-tech features do it all.

- Faxes can be scanned and sent electronically to recipients with verification of sender
- Thanks to protected memory, saved faxes and device settings are never lost if power is interrupted
- When receiving data, the F116 automatically reduces a document to fit the loaded paper size in tray
- "Intelligent" consumables let users know when toner is low

Compact and convenient Efficiency simplifies your workday.

- Well suited for a countertop or desktop use in offices where space is at a premium
- Extra tray option meets the needs of high-volume users
- Easy-to-use keypad makes it a breeze to perform any function
- Text messaging to fax for communication convenience

